

2021 Vision Systems Design Innovators Awards

SILVER HONOREE

Lens en onnect®

Motorized FA lens that can be operated easily with a single USB cable



Remote adjustment in out-of-reach places and inside



Precise adjustments that don't rely on feeling by-hand



Changing the focus point and changeover for workpieces at different heights



Perfect for embedded systems

- Focus, Iris, and Zoom can be controlled via USB
- Easy operation in areas where manual adjustment is not possible
- The stepping motor makes precise control possible
- Plug-and-play for easy deployment





LENS CONNECT series | LINE UP

BH series

DL0828UC-MPY	
Focal Length	8mm
F-number	F2.8 - F16.0
Working Distance	0.1m - Inf
Angle of View (1/1.1")	69.4° x 53.8° (D 80.4°)
Mount	С
Sensor size	1/1.1"
Resolution	12MP
Filter size	M52 P=0.75mm
Dimensions	φ 59.5mm x 63.3mm
Weight	178g

DL1224UC-MPY	
Focal Length	12mm
F-number	F2.4 - F16.0
Working Distance	0.1m - Inf
Angle of View (1/1.1")	50.5° x 38.1° (D 60.2°)
Mount	С
Sensor size	1/1.1"
Resolution	12MP
Filter size	M35.5 x P0.5mm
Dimensions	φ 59.5mm x 57.9mm
Weight	163g

_	DL1623UC-MPY	
	Focal Length	16mm
	F-number	F2.3 - F16.0
	Working Distance	0.11m - Inf
	Angle of View (1/1.1")	38.9° x 29.0° (D 47.0°)
	Mount	С
	Sensor size	1/1.1"
	Resolution	12MP
	Filter size	M35.5 x P0.5mm
	Dimensions	φ 59.5mm x 59.2mm
	Weight	173g

DL2523UC-MPY	
Focal Length	25mm
F-number	F2.3 - F16.0
Working Distance	0.12m - Inf
Angle of View (1/1.1")	253° x 18.7° (D 31.0°)
Mount	С
Sensor size	1/1.1"
Resolution	12MP
Filter size	M30.5 x P0.5mm
Dimensions	φ 59.5mm x 56.9mm
Weight	166g

DL3525UC-MPY	
Focal Length	35mm
F-number	F2.5 - F16.0
Working Distance	0.16m - Inf
Angle of View (1/1.1")	18.2° x 13.4° (D 22.5°)
Mount	С
Sensor size	1/1.1"
Resolution	12MP
Filter size	M30.5 x P0.5mm
Dimensions	φ 59.5mm x 57.9mm
Weight	160g

DL5028UC-MPY	
Focal Length	50mm
F-number	F2.8 - F16.0
Working Distance	0.2m - Inf
Angle of View (1/1.1")	13.2° x 9.7° (D 16.3°)
Mount	Ċ
Sensor size	1/1.1"
Resolution	12MP
Filter size	M30.5 x P0.5mm
Dimensions	φ 59.5mm x 58mm
Weight	173g

EL3Z0416UCS-MPWIR

Focal Length

F-number
Working Distance

VL6Z1626UC-MPYIR	
Focal Length	16mm - 96mm
F-number	F2.6 - F16C
Working Distance	3m - Inf
Angle of View (1.1")	Wide 48.1° x 35.6° (D 58.9°)
	Tele 8.5° x 6.3° (D 10.4°)
Mount	С
Sensor size	1.1"
Resolution	12MP
Filter size	M67xP0.75
Dimensions	78.2mm x 83.8 x 108.96mm
Weight	330g

EL6Z0915UCS-MPWIR	
Focal Length	9mm - 50mm
F-number	F1.5 - F16C
Working Distance	3m - Inf
Angle of View (1/1.8")	Wide 46.1° x 26.3° (D 52.5°)
	Tele 9.0° x 5.2° (D 10.2°)
Mount	CS
Sensor size	1/1.8"
Resolution	5MP
Filter size	*M67xP0.75 (With VM0918)
Dimensions	78.2mm x 83.8 x 104.8mm
Weight	299g

Working Distance	0.2m- Inf
Angle of View (1/1.8")	Wide 115.9° x 61.7° (D 138.1°)
	Tele 46.0° x 25.8° (D 52.9°)
Mount	CS
Sensor size	1/1.8"
Resolution	5MP
Filter size	*M55 x P0.75 (With VM0418)
Dimensions	φ 66mm x 59mm
Weight	161g

(*) There is no filter mount on the top of the lens For using filters, please attach VM0918.

(*) There is no filter mount on the top of the lens For using filters, please attach VMO418.

4.0mm - 10mm F1.6 - F16C

RF series

VL0826U-MPZ	
Focal Length	8mm
F-number	F2.6 - F16.0
Working Distance	0.1m - Inf
Angle of View (1")	76.9° x 61.5° (D 88.8°)
Mount	С
Sensor size	1"
Resolution	20MP
Filter size	*M82 x P0.75mm (With ZM0810)
Dimensions	φ 78mm x 52.93mm
Weight	334g
(*	There is no filter mount on the top of the lens

(*)	There is no filter mount on the top of the lens
	For using filters, please attachZM0810

VL1226U-MPZ	
Focal Length	12mm
F-number	F2.6 - F16.0
Working Distance	0.1m - Inf
Angle of View (1")	56.7° x 44.1° (D 67.4°)
Mount	С
Sensor size	1"
Resolution	20MP
Filter size	M46 x P0.75mm
Dimensions	φ 75mm x 48.5mm
Weight	273g
	7 //

VL1624U-MPZ		
Focal Length	16mm	
F-number	F2.6 - F16.0	
Working Distance	0.1m - Inf	
Angle of View (1")	43.8° x 336° (D 53.2°)	
Mount	С	
Sensor size	1"	
Resolution	20MP	
Filter size	M43 x P0.75mm	
Dimensions	φ 75mm x 52mm	
Weight	280g	

VL2520U-MPZ	
Focal Length	25mm
F-number	F2.6 - F16.0
Working Distance	0.15m - Inf
Angle of View (1")	28.8° x 21.8° (D 35.5°)
Mount	С
Sensor size	1"
Resolution	20MP
Filter size	M46 x P0.75mm
Dimensions	φ 78mm x 47mm
Weight	257g

VL5024U-MPZ		
Focal Length	50mm	
F-number	F2.4 - F16.0	
Working Distance	0.2m - Inf	
Angle of View (1")	14.6° x 11.0° (D 18.2°)	
Mount	С	
Sensor size	1"	
Resolution	20MP	
Filter size	M43 x P0.75mm	
Dimensions	φ 75mm x 66.5mm	
Weight	326g	

CBC Co., Ltd.

VL3522U-MPZ	
Focal Length	35mm
F-number	F2.2 - F16.0
Working Distance	0.2m - Inf
Angle of View (1")	20.8° x 15.7° (D 25.8°)
Mount	С
Sensor size	1"
Resolution	20MP
Filter size	M43 x P0.75mm
Dimensions	φ 75mm x 66.1mm
Weight	313g

VL7531U-MPZ		
Focal Length	75mm	
F-number	F3.1 - F16	
Working Distance	0.25m - Inf	
Angle of View (1")	9.8° x 7.3° (D 12.2°)	
Mount	С	
Sensor size	1"	
Resolution	20MP	
Filter size	M43 x P0.75mm	
Dimensions	φ 75mm x 87mm	
Weight	TBD	



https://www.computar-global.com/ product/bh/



https://www.computar-global.com/ product/rf/

Specification is subject to change without any notice.



Industrial Optics Division